

(19) World Intellectual Property
Organization
International Bureau



549400

(43) International Publication Date
30 September 2004 (30.09.2004)


PCT

(10) International Publication Number
WO 2004/082441 A2

- (51) International Patent Classification⁷: **A47G**
- (21) International Application Number:
PCT/US2004/007746
- (22) International Filing Date: 11 March 2004 (11.03.2004)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
10/389,733 14 March 2003 (14.03.2003) US
10/712,170 12 November 2003 (12.11.2003) US
- (71) Applicants and
(72) Inventors: **CITRYNELL, Andrew** [US/US]; 264 Sunrise Lane, Carbondale, Colorado 81623 (US). **MILLER, Kimberly, Ann** [US/US]; 264 Sunrise Lane, Carbondale, Colorado 81623 (US). **SCHWARZE, Joel** [US/US]; 19266 Sioux Hills Rd., Hutchinson, Minnesota 55350 (US).
- (74) Agents: **GIBBY, Darin, J. et al.**; Townsend and Townsend and Crew LLP, Two Embarcadero Center, Eighth Floor, San Francisco, California 94111-3834 (US).
- (81) Designated States (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR,

[Continued on next page]

(54) Title: DRINKING VESSELS WITH REMOVABLE COOLING DEVICES



(57) Abstract: In one embodiment, a beverage container comprises a vessel having an interior that is adapted to hold a beverage. The vessel has a closed bottom end and an open top end. The bottom end defines a cavity that is fluidly sealed from the interior of the vessel. A cooling element is configured to be coupled to the vessel and to fit within the cavity. A base comprises a bottom member and a stem extending vertically upward from the bottom member. The base includes a connector that is configured to be coupled to the cooling element or vice versa.

WO 2004/082441 A2



GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK,
TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW,
ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

- *without international search report and to be republished upon receipt of that report*